

Description

stud thread: 10-32, 6 studs, plastic board, last number indicates number of studs, MS27212 series board

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2721226
Minimum Qty (MOQ):	1
NSN:	5940-00-028-8004
Schedule B:	8535.10.9090
ECCN:	EAR99
National Motor Freight:	061045, Boards Printed Circuit Elec



* See page 2 for technical characteristics

P/N MS27212-2-6 Specifications

Mounting Hole Diameter:	0.115 Inches
Body Style:	Barrier Standoff
Terminal Row Quantity:	1
Center To Center Distance Between Terminals:	0.750 Inches
Board Construction:	Hollow Construction Without Insulated Strip
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.750 Inches
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:	0.469 Inches
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:	0.218 Inches
Board Overall Length:	4.936 Inches
Board Overall Width:	0.938 Inches
Board Overall Height:	1.079 Inches
Board Height Excluding Terminals:	0.789 Inches
Base Thickness:	0.328 Inches
Mounting Facility Type And Quantity:	7 Unthreaded Hole
Nonfeedthru Terminal Type:	597 Single
Nonfeedthru Terminal Quantity:	6 Single
Terminal Pattern Arrangement:	Single Row
Terminal Design:	Nonfeedthru
Material:	Plastic Diallyl Phthalate Board And Glass Fiber Board
Material:	Steel Comp 303 Terminals
Material Document And Classification:	Mil-p-19833 Mil Spec All Material Responses Board
Material Document And Classification:	Qq-s-763,cond A Fed Spec Single Material Response Terminals

How to Order

Order this terminal board from our inventory online by visiting <https://military-fasteners.com/electrical/terminal+boards/MS27212-2-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.