

## P/N MS27212-4-2

## **Description**

MS27212-4-2 Terminal Board

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2721242

Minimum Qty (MOQ):

NSN: 5940-00-028-8005

ECCN: EAR99

National Motor Freight: 156600, Plastic / Rubber Article Viz:



# P/N MS27212-4-2 Specifications

Mounting Hole Diameter:	0.141 Inches
Body Style:	Barrier Standoff
Terminal Row Quantity:	1
Center To Center Distance Between Terminals:	1.500 Inches
Board Construction:	Hollow Construction Without Insulated Strip
Center To Center Distance Between Mounting Facilities Parallel To Length:	1.500 Inches
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:	0.625 Inches
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:	0.312 Inches
Board Overall Length:	3.624 Inches
Board Overall Width:	1.250 Inches
Board Overall Height:	1.392 Inches
Board Height Excluding Terminals:	1.297 Inches
Base Thickness:	0.408 Inches
Mounting Facility Type And Quantity:	3 Unthreaded Hole
Nonfeedthru Terminal Type:	597 Single
Nonfeedthru Terminal Quantity:	2 Single
Terminal Pattern Arrangement:	Single Row
Terminal Design:	Nonfeedthru
Material:	Plastic Diallyl Phthalate Board And Glass Fiber Board
Material:	Steel Comp 303 Terminals
Material Document And Classification:	Mil-p-19833 Mil Spec All Material Responses Board
Material Document And Classification:	Qq-s-763,cond A Fed Spec Single Material Response Terminals

### **How to Order**

Order this terminal board from our inventory online by visiting <a href="https://military-fasteners.com/electrical/terminal+board+covers/MS27212-4-2">https://military-fasteners.com/electrical/terminal+board+covers/MS27212-4-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/electrical/terminal+board+covers/MS27212-4-2">https://military-fasteners.com/electrical/terminal+board+covers/MS27212-4-2</a> and selecting the