

Description

Stud thread: 8-32, last number indicates number of studs, MS27212 series terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2721266
Minimum Qty (MOQ):	2
NSN:	5940-01-105-8085
Schedule B:	8537.10.9090
ECCN:	EAR99



P/N MS27212-6-6 Specifications

Dielectric Withstanding Voltage In Volts:	2500.0
Body Style:	Barrier Standoff
Terminal Row Quantity:	1
Center To Center Distance Between Terminals:	0.750 Inches
Board Construction:	Solid Construction
Board Overall Length:	4.474 Inches
Board Overall Width:	0.780 Inches
Board Overall Height:	1.005 Inches
Board Height Excluding Terminals:	0.625 Inches
Base Thickness:	0.281 Inches
Nonfeedthru Terminal Type:	597 Single
Nonfeedthru Terminal Quantity:	6 Single
Terminal Pattern Arrangement:	Single Row
Terminal Design:	Nonfeedthru
Material:	Plastic Diallyl Phthalate Board And Glass Fiber Board
Material:	Steel Corrosion Resisting Terminals
Material Document And Classification:	Mil-p-19833 Mil Spec All Material Responses Board

How to Order

Order this terminal board from our inventory online by visiting <https://military-fasteners.com/electrical/terminal+boards/MS27212-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.