

## Description

Stud thread: 8-32, last number indicates number of studs, MS27212 series terminal

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS2721266
Minimum Qty (MOQ):	2
NSN:	5940-01-105-8085
Schedule B:	8537.10.9090
ECCN:	EAR99



## P/N MS27212-6-6 Specifications

<b>Dielectric Withstanding Voltage In Volts:</b>	2500.0
<b>Body Style:</b>	Barrier Standoff
<b>Terminal Row Quantity:</b>	1
<b>Center To Center Distance Between Terminals:</b>	0.750 Inches
<b>Board Construction:</b>	Solid Construction
<b>Board Overall Length:</b>	4.474 Inches
<b>Board Overall Width:</b>	0.780 Inches
<b>Board Overall Height:</b>	1.005 Inches
<b>Board Height Excluding Terminals:</b>	0.625 Inches
<b>Base Thickness:</b>	0.281 Inches
<b>Nonfeedthru Terminal Type:</b>	597 Single
<b>Nonfeedthru Terminal Quantity:</b>	6 Single
<b>Terminal Pattern Arrangement:</b>	Single Row
<b>Terminal Design:</b>	Nonfeedthru
<b>Material:</b>	Plastic Diallyl Phthalate Board And Glass Fiber Board
<b>Material:</b>	Steel Corrosion Resisting Terminals
<b>Material Document And Classification:</b>	Mil-p-19833 Mil Spec All Material Responses Board

## How to Order

Order this terminal board from our inventory online by visiting <https://military-fasteners.com/electrical/terminal+boards/MS27212-6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.