



Military-Fasteners.com

P/N MS27407-4

Description


3 position, 2 pole standard lever, screw terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS274074
Minimum Qty (MOQ):	1
NSN:	5930-00-445-9274
ECCN:	9A991
National Motor Freight:	061300, Circuit Breaker / Switch Noi



* See page 2 for technical characteristics

P/N MS27407-4 Specifications

Thread Class:	2b
Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Dustproof
Bushing Length:	0.470 Inches Nominal
Body Length:	1.340 Inches Nominal
Body Width:	0.890 Inches Nominal
Body Height:	1.370 Inches Nominal
Case Material:	Metal
Actuator Style:	Round
Actuator Diameter:	0.240 Inches Nominal
Actuator Height:	0.680 Inches Nominal
Actuator Position-action Relationship:	Up Position Maintained And Down Position Maintained And Center Position Maintained
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Mounting Surface To Terminal End Distance:	1.350 Inches Nominal
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	2 Pole, Double Throw, Three Positions Maintained Single Switch Unit
Contact Load Current Rating At Maximum Rated Voltage:	20.000 Amperes Resistive Dc And 15.000 Amperes Inductive Dc And 7.000 Amperes Lamp Dc And 25.000 Amperes Resistive Ac And 15.000 Amperes Inductive Ac And 4.000 Amperes Lamp Ac
Thread Series Designator:	Uns
Terminal Type And Quantity:	6 Tab W/screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/electrical/toggle+switches/MS27407-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.