

Description

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27576310
Minimum Qty (MOQ):	2
NSN:	5306-00-486-5596
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS27576-3-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.236 Inches Minimum And 0.318 Inches Maximum
Fastener Length:	0.997 Inches Minimum And 1.017 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.095 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Locking Feature:	Detent Ball Grip
Grip Diameter:	0.1885 Inches Minimum And 0.1894 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.625 Inches Minimum And 0.641 Inches Maximum
Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.914 Inches Minimum First Hole And 0.934 Inches Maximum First Hole
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS27576-3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.