

**Description**

Fastener Length: 0-63/64", Thread: 10-32, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27576310
Minimum Qty (MOQ):	2
NSN:	5306-00-486-5596
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS27576-3-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.236 Inches Minimum And 0.318 Inches Maximum
<b>Fastener Length:</b>	0.997 Inches Minimum And 1.017 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.095 Inches Minimum And 0.110 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Locking Feature:</b>	Detent Ball Grip
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1894 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.625 Inches Minimum And 0.641 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.914 Inches Minimum First Hole And 0.934 Inches Maximum First Hole
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 6150 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS27576-3-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.