

**Description**

Fastener Length: 1-13/64", Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27576313
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-429-1782
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS27576-3-13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.237 Inches Minimum And 0.319 Inches Maximum
<b>Fastener Length:</b>	1.185 Inches Minimum And 1.205 Inches Maximum
<b>Head Height:</b>	0.095 Inches Minimum And 0.110 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1894 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Special Features:</b>	W/retaining Element On Shank
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-b-83050 Mil Spec Single Material Response Overall

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS27576-3-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.