

P/N MS27576-3-22

Military-Fasteners.com

Description

Fastener Length: 1-49/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS27576322
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-486-5597
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS27576-3-22 Specifications

d Direction:	Right-hand
d Length:	0.236 Inches Minimum And 0.318 Inches Maximum
ner Length:	1.747 Inches Minimum And 1.767 Inches Maximum
Style:	Dished Hexagon
Height:	0.095 Inches Minimum And 0.110 Inches Maximum
Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
ig Feature:	Detent Ring Grip
iameter:	0.1885 Inches Minimum And 0.1894 Inches Maximum
Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
al Thread Diameter:	0.190 Inches
ength:	1.375 Inches Minimum And 1.391 Inches Maximum
d Quantity Per Inch:	32
um Tensile Strength:	95000 Pounds Per Square Inch
ess Rating:	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
ce From Head Largest Bearing Surface To Shank Center:	1.654 Inches Minimum First Hole And 1.684 Inches Maximum First Hole
e Finish:	63.0 Microinches Bearing Surface Of Head
e Finish:	63.0 Microinches Grip
	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 6150 Overall
e Treatment:	Cadmium Overall And Chromate Overall
e Treatment Document And Classification:	Qq-p-416 Ty 2 Class 2 Fed Spec Single Treatment Response Overall
d Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS27576-3-22</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.