

**Description**

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS27576409                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-138-6385                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS27576-4-09 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.283 Inches Minimum And 0.334 Inches Maximum                       |
| <b>Fastener Length:</b>   | 0.981 Inches Minimum And 1.001 Inches Maximum                       |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.126 Inches Minimum And 0.141 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.2483 Inches Minimum And 0.2492 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches  |
| <b>Grip Length:</b>   | 0.562 Inches Minimum And 0.578 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 28  |
| <b>Hardness Rating:</b>   | 36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.881 Inches Minimum First Hole And 0.911 Inches Maximum First Hole |
| <b>Surface Finish:</b>  | 63.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>  | 63.0 Microinches Grip   |
| <b>Special Features:</b>  | W/retaining Element On Shank  |
| <b>Material:</b>  | Steel Overall   |
| <b>Material Document And Classification:</b>                            | -11-b-83050 Mil Spec Single Material Response Overall               |
| <b>Surface Treatment:</b>   | Cadmium Overall And Chromate Overall                                |
| <b>Thread Series Designator:</b>  | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS27576-4-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.