

P/N MS27576-5-10

Description

Fastener Length: 1-7/64", Thread: 1/4-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS27576510

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-097-4268

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS27576-5-10 Specifications

Ba
Right-hand
0.311 Inches Minimum And 0.378 Inches Maximum
1.103 Inches Minimum And 1.123 Inches Maximum
Crowned Hexagon
0.157 Inches Minimum And 0.172 Inches Maximum
0.492 Inches Minimum And 0.502 Inches Maximum
0.310 Inches Minimum And 0.311 Inches Maximum
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
0.312 Inches
1.223 Inches Minimum And 1.274 Inches Maximum
24
0.988 Inches Minimum First Hole And 1.018 Inches Maximum First Hole
63.0 Microinches Bearing Surface Of Head
63.0 Microinches Grip
W/retaining Element On Shank
Steel Overall
Mil-b-83050 Mil Spec Single Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS27576-5-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.