

P/N MS27576-5-22

Description

Fastener Length: 1-55/64", Thread: 1/4-24, Thread Length: 3/8

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

 SKU / Model:
 MS27576522

 Minimum Qty (MOQ):
 1

 NSN:
 5306-00-001-4807

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS27576-5-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.311 Inches Minimum And 0.378 Inches Maximum
Fastener Length:	1.853 Inches Minimum And 1.873 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.157 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3108 Inches Minimum And 0.3117 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.375 Inches Minimum And 1.391 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank	1.738 Inches Minimum First Hole And 1.768 Inches Maximum First Hole
Hole Center:	1.738 Inches Minimum First Hole And 1.768 Inches Maximum First Hole
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Bearing Surface Of Head 63.0 Microinches Grip
Surface Finish: Surface Finish: Special Features:	63.0 Microinches Bearing Surface Of Head 63.0 Microinches Grip W/retaining Element On Shank Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Surface Finish: Surface Finish: Special Features: Material:	63.0 Microinches Bearing Surface Of Head 63.0 Microinches Grip W/retaining Element On Shank Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 6150 Overall

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS27576-5-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS27576-5-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/MS27576-5-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/ms27576-5-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/ms27576-5-22 and selecting the quantity you want the properties of the proper