

Description

Fastener Length: 2-7/64", Thread: 3/8-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27576625
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-014-7284
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS27576-6-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.357 Inches Minimum And 0.439 Inches Maximum
Fastener Length:	2.101 Inches Minimum And 2.121 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.189 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3733 Inches Minimum And 0.3742 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.562 Inches Minimum And 1.578 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.986 Inches Minimum First Hole And 2.016 Inches Maximum First Hole
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Special Features:	Retaining Element In Shank
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS27576-6-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.