

**Description**

Fastener Length: 4-23/32", Thread: 1/2-20, Thread Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27576865
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-460-8549
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS27576-8-65 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.401 Inches Minimum And 0.546 Inches Maximum
<b>Fastener Length:</b>	4.708 Inches Minimum And 4.728 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.251 Inches Minimum And 0.266 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4982 Inches Minimum And 0.4991 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	4.062 Inches Minimum And 4.078 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	4.458 Inches Minimum First Hole And 4.618 Inches Maximum First Hole
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Special Features:</b>	W/retaining Element On Shank
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS27576-8-65> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.