

P/N MS27645-6

Description

heavy duty double row anti-friction airframe bearing

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS276456

Minimum Qty (MOQ):

NSN: 3110-00-042-4810

ECCN: EAR99

National Motor Freight: 114820, Bearings / Bushings Noi Ball / Roller



^{*} See page 2 for technical characteristics

P/N MS27645-6 Specifications

Bore Diameter:	0.3750 Inches Nominal
Overall Outside Diameter:	1.4375 Inches Nominal
Lubrication Material:	Grease
Outer Ring Width:	0.4690 Inches Nominal
Inner Ring Width:	0.6200 Inches Nominal
Seal Quantity:	2
Bearing Seal Type:	Contact
Alignment Type:	Self-aligning Self-aligning
Load Direction:	Radial
Self-alignment Location:	Internal
Standard Tolerance Designation:	Afbma Std Tolerance For Airframe Ball Bearings
Special Features:	80 Pct. Full Of Mil-g-81322,axial Play 0.030 In. Max.,heat Treat Rings And Balls To Rockwell C 60 To 66 And Stabilized For Operation At 250 Deg.f,10 Deg Self-aligning In Either Direction
Lubrication Material Document And Classification:	Mil-g-81322 Mil Spec Single Material Response
Material:	Plastic Polytetrafluoroethylene Seal
Material:	Steel Comp E51100 Ball Or Steel Comp E52100 Ball
Material:	Steel Comp E52100 Inner Ring
Material:	Steel Comp E52100 Outer Ring
Material:	Steel Corrosion Resisting Retainer
Material Document And Classification:	66 Fed Std All Material Responses Ball
Material Document And Classification:	66 Fed Std Single Material Response Inner Ring
Material Document And Classification:	66 Fed Std Single Material Response Outer Ring
Material Document And Classification:	Ams 3652 Assn Std Single Material Response Seal Or Ams 3666 Assn Std Single Material Response Seal
Surface Treatment:	Cadmium Exposed Surfaces As Mounted
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 2 Fed Spec Single Treatment Response Exposed Surfaces As Mounted
Style Designator:	Single Row Self Aligning Single Row Inner Ring Extended Both Sides

How to Order

