

## P/N MS27647-4

### **Description**

intermediate duty, double row, extra wide, anti-friction, airframe use, MS27647 series bearing

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### DW4KFS464

SKU / Model: MS276474

Minimum Qty (MOQ):

NSN: 3110-00-277-8348

Schedule B: 8482.10.1080

ECCN: EAR99

National Motor Freight: 114820, Bearings / Bushings Noi Ball / Roller









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS27647-4 Specifications

Bore Diameter:	0.2495 Inches Minimum And 0.2500 Inches Maximum
Overall Outside Diameter:	0.7495 Inches Minimum And 0.7500 Inches Maximum
Lubrication Material:	Grease
Outer Ring Width:	0.7450 Inches Minimum And 0.7500 Inches Maximum
Inner Ring Width:	0.8700 Inches Minimum And 0.8750 Inches Maximum
Seal Quantity:	2
Bearing Seal Type:	Contact
Load Direction:	Radial
Part Name Assigned By Controlling Agency:	Bearing Ball, Airframe, Anti Friction, Extra Wide Double Row, Intermediate Duty
Special Features:	M80 Pct Full Of Grease Mil-g-81322,heat Treat Rings And Balls To Rockwell C Scale 60 To 66 And Heat Stabilized For Operation At 250 Deg F,radial And Lateral Eccentricity 0.0010 In. Inner Ring,0.0016 In. Outer Ring
Lubrication Material Document And Classification:	Mil-g-81322 Mil Spec Single Material Response
Material:	Plastic Polytetrafluoroethylene Seal
Material:	Steel Comp E52100 Ball
Material:	Steel Comp E52100 Inner Ring
Material:	Steel Comp E52100 Outer Ring
Material Document And Classification:	Ams 3652 Assn Std Single Material Response Seal
Material Document And Classification:	Ams 6440 Assn Std Single Material Response Ball
Material Document And Classification:	Ams 6440 Assn Std Single Material Response Inner Ring
Material Document And Classification:	Ams 6440 Assn Std Single Material Response Outer Ring
Surface Treatment:	Cadmium All External/exposed Metal Surfaces
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl2 Fed Spec Single Treatment Response All External/exposed Metal Surfaces
Style Designator:	Double Row

## **How to Order**

