

**Description**

inner diameter: 0.070", thickness: 0.070", preformed packing hydraulic o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS28775004
Minimum Qty (MOQ):	25
NSN:	5331-00-585-9771
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS28775-004 Specifications

<b>Outside Diameter:</b>	0.210 Inches Nominal
<b>Temp Rating:</b>	275.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.067 Inches Minimum And 0.071 Inches Maximum
<b>Center Hole Diameter:</b>	0.065 Inches Minimum And 0.075 Inches Maximum
<b>Elongation Percentage:</b>	160 Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr
<b>Material Document And Classification:</b>	Mil-p-25732 Mil Spec Single Material Response

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS28775-004](https://military-fasteners.com/o_rings/o_rings/MS28775-004) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.