

**Description**

inner diameter: 0.612, thickness: 0.103", preformed packing, hydraulic use, MS28775 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS28775114
Minimum Qty (MOQ):	50
NSN:	5331-00-618-0801
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS28775-114 Specifications

<b>Outside Diameter:</b>	0.803 Inches Minimum And 0.833 Inches Maximum
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	0.607 Inches Minimum And 0.617 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS28775-114](https://military-fasteners.com/o_rings/o_rings/MS28775-114) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.