

# P/N MS28775-123

### **Description**

inner diameter: 1.174, thickness: 0.103", preformed packing, hydraulic

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS28775123

Minimum Qty (MOQ): 25

NSN: 5331-00-618-3754

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS28775-123 Specifications

Outside Diameter:	1.362 Inches Minimum And 1.398 Inches Maximum
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	1.168 Inches Minimum And 1.180 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS28775-123">https://military-fasteners.com/o\_rings/o\_rings/MS28775-123</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-123">https://military-fasteners.com/o\_rings/MS28775-123</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-123">https://military-fasteners.com/o\_rings/MS28775-123</a> and selecting the quantity you want then click "add to cart".