

**Description**

inner diameter: 1.424, thickness: 0.103", preformed packing, hydraulic use, MS28775 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS28775127
Minimum Qty (MOQ):	50
NSN:	5331-00-813-2806
Schedule B:	4016.93.5010
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS28775-127 Specifications

<b>Outside Diameter:</b>	1.612 Inches Minimum And 1.648 Inches Maximum
<b>Temp Rating:</b>	275.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	1.418 Inches Minimum And 1.430 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr
<b>Material Document And Classification:</b>	Mil-p-25732 Mil Spec Single Material Response

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS28775-127](https://military-fasteners.com/o_rings/o_rings/MS28775-127) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.