

## Description

inner diameter: 1.109, thickness: 0.139", preformed packing, hydraulic use, MS28775 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS28775216
Minimum Qty (MOQ):	50
NSN:	5331-00-641-0231
Schedule B:	4016.99.6050
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS28775-216 Specifications

<b>Outside Diameter:</b>	1.367 Inches Minimum And 1.407 Inches Maximum
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	1.103 Inches Minimum And 1.115 Inches Maximum
<b>End Item Identification:</b>	Nsn 2320-01-304-2277 Pls (palletized Loading System)
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS28775-216](https://military-fasteners.com/o_rings/o_rings/MS28775-216) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.