

## P/N MS28775-226

## **Description**

inner diameter: 1.980, thickness: 0.139", preformed packing hydraulic

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS28775226

Minimum Qty (MOQ): 25

NSN: 5331-00-576-9732

Schedule B: 4016.93.5010

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









# P/N MS28775-226 Specifications

Outside Diameter:	2.236 Inches Minimum And 2.288 Inches Maximum
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	1.974 Inches Minimum And 1.994 Inches Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS28775-226">https://military-fasteners.com/o\_rings/o\_rings/MS28775-226</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-226">https://military-fasteners.com/o\_rings/o\_rings/MS28775-226</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-226">https://military-fasteners.com/o\_rings/o\_rings/MS28775-226</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-226">https://military-fasteners.com/o\_rings/MS28775-226</a> and selecting the quantity you want then click "add to cart".