

Description

inner diameter: 2.609, thickness: 0.139", preformed packing hydraulic o-ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS28775231 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5331-01-246-3902 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



* See page 2 for technical characteristics

P/N MS28775-231 Specifications

| | |
|--|---|
| Outside Diameter: | 2.859 Inches Minimum And 2.915 Inches Maximum |
| Temp Rating: | -65.0 Deg Fahrenheit And 225.0 Deg Fahrenheit |
| Cross-sectional Height: | 0.135 Inches Minimum And 0.143 Inches Maximum |
| Center Hole Diameter: | 2.589 Inches Minimum And 2.629 Inches Maximum |
| Hardness Rating: | 75.0 Shore Durometer A Nominal |
| Criticality Code Justification: | Adyt |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr |

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS28775-231 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.