

**Description**

inner diameter: 2.609, thickness: 0.139", preformed packing hydraulic o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS28775231
Minimum Qty (MOQ):	25
NSN:	5331-01-246-3902
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS28775-231 Specifications

<b>Outside Diameter:</b>	2.859 Inches Minimum And 2.915 Inches Maximum
<b>Temp Rating:</b>	-65.0 Deg Fahrenheit And 225.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.135 Inches Minimum And 0.143 Inches Maximum
<b>Center Hole Diameter:</b>	2.589 Inches Minimum And 2.629 Inches Maximum
<b>Hardness Rating:</b>	75.0 Shore Durometer A Nominal
<b>Criticality Code Justification:</b>	Adyt
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS28775-231](https://military-fasteners.com/o_rings/o_rings/MS28775-231) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.