

P/N MS28775-231

Description

inner diameter: 2.609, thickness: 0.139", preformed packing hydraulic o-ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information


SKU / Model: MS28775231

Minimum Qty (MOQ): 10

NSN: 5331-01-246-3902

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



^{*} See page 2 for technical characteristics

P/N MS28775-231 Specifications

Outside Diameter:	2.859 Inches Minimum And 2.915 Inches Maximum
Temp Rating:	-65.0 Deg Fahrenheit And 225.0 Deg Fahrenheit
Cross-sectional Height:	0.135 Inches Minimum And 0.143 Inches Maximum
Center Hole Diameter:	2.589 Inches Minimum And 2.629 Inches Maximum
Hardness Rating:	75.0 Shore Durometer A Nominal
Criticality Code Justification:	Adyt
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS28775-231 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/o_rings/MS28775-231 and selecting the quantity you want then click out https://military-fasteners.com/o_rings/o_rings/MS28775-231 and selecting the quantity you want then click out https://military-fasteners.com/o_rings/o_rings/MS28775-231 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS28775-231 and selecting the quantity you want then click "add to cart".