

## P/N MS28775-331

### **Description**

inner diameter: 2.225, thickness: 0.210", preformed packing, hydraulic, MS28775 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS28775331

Minimum Qty (MOQ): 25

NSN: 5331-00-584-1186

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS28775-331 Specifications

Outside Diameter:	2.617 Inches Minimum And 2.673 Inches Maximum
Cross-sectional Height:	0.205 Inches Minimum And 0.215 Inches Maximum
Center Hole Diameter:	2.215 Inches Minimum And 2.235 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS28775-331">https://military-fasteners.com/o\_rings/o\_rings/MS28775-331</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-331">https://military-fasteners.com/o\_rings/o\_rings/MS28775-331</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-331">https://military-fasteners.com/o\_rings/o\_rings/MS28775-331</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS28775-331">https://military-fasteners.com/o\_rings/MS28775-331</a> and selecting the quantity you want then click "add to cart".