



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N MS28775-334**

## Description

inner diameter: 2.60, thickness: 0.21", preformed packing, hydraulic, MS28775 series oring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS28775334
Minimum Qty (MOQ):	10
NSN:	5331-00-292-0578
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS28775-334 Specifications

<b>Outside Diameter:</b>	2.990 Inches Minimum And 3.050 Inches Maximum
<b>Temp Rating:</b>	275.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.205 Inches Minimum And 0.215 Inches Maximum
<b>Center Hole Diameter:</b>	2.590 Inches Minimum And 2.610 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr
<b>Material Document And Classification:</b>	Mil-p-25732 Mil Spec Single Material Response

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS28775-334](https://military-fasteners.com/o_rings/o_rings/MS28775-334) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.