

Description

outer diameter: 3/4, preformed packing, straight thread tube fitting, temperature range -65 to 212 degrees, MS28778 series o-ring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2877812
Minimum Qty (MOQ):	20
NSN:	5331-00-251-8839
Schedule B:	4016.93.0000
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N MS28778-12 Specifications

Outside Diameter:	1.139 Inches Minimum And 1.173 Inches Maximum
Temp Rating:	-65.0 Deg Fahrenheit And 180.0 Deg Fahrenheit
Cross-sectional Height:	0.112 Inches Minimum And 0.120 Inches Maximum
Center Hole Diameter:	0.918 Inches Minimum And 0.930 Inches Maximum
Hardness Rating:	90.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr
Material Document And Classification:	Mil-p-5510 Mil Spec Single Material Response

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS28778-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.