

**Description**

5000 psi, high pressure, MS28889 series valve

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS288892
Minimum Qty (MOQ):	1
NSN:	4820-00-535-6483
Schedule B:	8481.20.0030
ECCN:	EAR99
National Motor Freight:	127220, Pressure Reg / Red / Relief Valves Noi



\* See page 2 for technical characteristics

## P/N MS28889-2 Specifications

<b>Body Material:</b>	Steel,cres,qq-s-764,comp. 303se
<b>Outside Surface Treatment:</b>	Passivated And Dichromate Treated
<b>Body Style:</b>	Straight Thru
<b>Stem Material:</b>	Steel,cres,qq-s-764,comp. 303se
<b>Furnished Items:</b>	Cap
<b>Temp Rating:</b>	Not Rated
<b>Media For Which Designed:</b>	Air Or Gas
<b>First End Connection Type:</b>	Threaded External Boss
<b>First End Style Designator:</b>	External Seat For Gasket Seal
<b>First End Thread Class:</b>	3a
<b>First End Thread Direction:</b>	Right-hand
<b>Second End Relationship With First End:</b>	Not Identical
<b>Second End Connection Type:</b>	Threaded External Tube
<b>Second End Style Designator:</b>	Hose Socket
<b>Second End Outside Diameter Tube Accommodated:</b>	0.125 Inches Nominal
<b>Second End Thread Class:</b>	3a
<b>Second End Thread Direction:</b>	Right-hand
<b>Seat Material:</b>	Steel,cres,qq-s-764,comp. 303se
<b>Flow Control Device:</b>	Stem And Integral Disk
<b>Flow Control Device Material:</b>	Steel,cres,qq-s-764,comp. 303se
<b>End Connection Quantity:</b>	2
<b>Core Environmental Protection:</b>	Corrosion
<b>Commercial Core Length Designator:</b>	Standard
<b>Spring Material:</b>	Steel, Qq-s-763, Class 303
<b>Commercial Spring Tension Rating:</b>	Not Rated
<b>Special Features:</b>	2 Lockwire Holes And 5000.0 Psi Operating Pressure

## How to Order

Order this pneumatic tank valve from our inventory online by visiting <https://military-fasteners.com/valves/pneumatic+tank+valves/MS28889-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.