

**Description**

5000 psi, high pressure, MS28889 series valve

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS288892
Minimum Qty (MOQ):	1
NSN:	4820-00-535-6483
Schedule B:	8481.20.0030
ECCN:	EAR99
National Motor Freight:	127220, Pressure Reg / Red / Relief Valves Noi



\* See page 2 for technical characteristics

# P/N MS28889-2 Specifications

Body Material:	Steel,cres,qq-s-764,comp. 303se
Outside Surface Treatment:	Passivated And Dichromate Treated
Body Style:	Straight Thru
Stem Material:	Steel,cres,qq-s-764,comp. 303se
Furnished Items:	Cap
Temp Rating:	Not Rated
Media For Which Designed:	Air Or Gas
First End Connection Type:	Threaded External Boss
First End Style Designator:	External Seat For Gasket Seal
First End Thread Class:	3a
First End Thread Direction:	Right-hand
Second End Relationship With First End:	Not Identical
Second End Connection Type:	Threaded External Tube
Second End Style Designator:	Hose Socket
Second End Outside Diameter Tube Accommodated:	0.125 Inches Nominal
Second End Thread Class:	3a
Second End Thread Direction:	Right-hand
Seat Material:	Steel,cres,qq-s-764,comp. 303se
Flow Control Device:	Stem And Integral Disk
Flow Control Device Material:	Steel,cres,qq-s-764,comp. 303se
End Connection Quantity:	2
Core Environmental Protection:	Corrosion
Commercial Core Length Designator:	Standard
Spring Material:	Steel, Qq-s-763, Class 303
Commercial Spring Tension Rating:	Not Rated
Special Features:	2 Lockwire Holes And 5000.0 Psi Operating Pressure

## How to Order

Order this pneumatic tank valve from our inventory online by visiting <https://military-fasteners.com/valves/pneumatic+tank+valves/MS28889-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.