

## P/N MS29512-02

## **Description**

Tubing outer diameter: 1/8, preformed packing, hydrocarbon fuel resistant, tube fitting, MS29512 series o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2951202

Minimum Qty (MOQ): 20

NSN: 5331-00-135-8622

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29512-02 Specifications

Outside Diameter:	0.356 Inches Minimum And 0.378 Inches Maximum
Cross-sectional Height:	0.061 Inches Minimum And 0.067 Inches Maximum
Center Hole Diameter:	0.234 Inches Minimum And 0.244 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/o\_rings/MS29512-02">https://military-fasteners.com/o\_rings/o\_rings/MS29512-02</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29512-02">https://military-fasteners.com/o\_rings/o\_rings/MS29512-02</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29512-02">https://military-fasteners.com/o\_rings/o\_rings/MS29512-02</a> and selecting the quantity you want then click "add to cart".