

## P/N MS29512-05

## **Description**

tubing outer diameter: 5/16, preformed packing o-ring, hydrocarbon fuel resistant - tube fitting

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2951205

Minimum Qty (MOQ): 50

NSN: 5331-00-263-8029

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29512-05 Specifications

Outside Diameter:	0.547 Inches Minimum And 0.569 Inches Maximum
Cross-sectional Height:	0.069 Inches Minimum And 0.075 Inches Maximum
Center Hole Diameter:	0.409 Inches Minimum And 0.419 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/0\_rings/MS29512-05">https://military-fasteners.com/o\_rings/o\_rings/MS29512-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29512-05">https://military-fasteners.com/o\_rings/o\_rings/MS29512-05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29512-05">https://military-fasteners.com/o\_rings/o\_rings/MS29512-05</a> and selecting the quantity you want then click "add to cart".