

Description

Tubing outer diameter: 3/4", preformed packing, hydrocarbon fuel resistant, tube fitting, MS29512 series o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2951212
Minimum Qty (MOQ):	50
NSN:	5331-00-263-8033
Schedule B:	4016.93.1010
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS29512-12 Specifications

<b>Outside Diameter:</b>	1.139 Inches Minimum And 1.173 Inches Maximum
<b>Cross-sectional Height:</b>	0.112 Inches Minimum And 0.120 Inches Maximum
<b>Center Hole Diameter:</b>	0.918 Inches Minimum And 0.930 Inches Maximum
<b>End Item Identification:</b>	W/s: Deep Submergence Systems Programs (dssp); Support Equipment, B-1 Aircraft; Armored Security Vehicle, Model Xm1117; Aircraft, Airlifter C-17a; Engine, Aircraft, Tf-33-p-7 (c-141a/b); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Engine, Aircraft Tf33-p-3/59 (c/ec-135, B-52h); Engine, Aircraft, T56-a-7/15 (c-130b/e/h/n/p); Aircraft, C-2a (reprocured); Torpedo Systems, Mk 50;hemtt Family (heavy Expanded Mobility Tactical Trucks)
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29512-12](https://military-fasteners.com/o_rings/o_rings/MS29512-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.