

# P/N MS29513-006

### **Description**

inner diameter: 0.114", thickness 0.070", preformed packing o-ring - hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513006

Minimum Qty (MOQ): 25

NSN: 5331-00-252-6048

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-006 Specifications

Outside Diameter:	0.243 Inches Minimum And 0.265 Inches Maximum
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.109 Inches Minimum And 0.119 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-006">https://military-fasteners.com/o\_rings/o\_rings/MS29513-006</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-006">https://military-fasteners.com/o\_rings/MS29513-006</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-006">https://military-fasteners.com/o\_rings/MS29513-006</a> and selecting the quantity you want then click "add to cart".