

Description

inner diameter: 0.176", thickness 0.070", preformed packing o-ring - hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513008
Minimum Qty (MOQ):	15
NSN:	5331-00-248-3833
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS29513-008 Specifications

Outside Diameter:	0.305 Inches Minimum And 0.327 Inches Maximum
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.171 Inches Minimum And 0.181 Inches Maximum
End Item Identification:	W/s: L.p. Compressors; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Radar Set An/tpn-18; Fire Control System, Missile Mk 74 (fcs); Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Fire Control System, Mk 92 (fcs); Air Compressors, High Pressure; Main Feed Pumps
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-008 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.