

Description

inner diameter: 0.239", thickness: 0.07", preformed packing, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513010
Minimum Qty (MOQ):	50
NSN:	5331-00-248-3835
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS29513-010 Specifications

Outside Diameter:	0.368 Inches Minimum And 0.390 Inches Maximum
Temp Rating:	-70.0 Deg Fahrenheit And 180.0 Deg Fahrenheit
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.234 Inches Minimum And 0.244 Inches Maximum
Hardness Rating:	70.0 Shore Durometer A Nominal
Special Features:	Od Is 0.375 In
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-010 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.