

Description

inner diameter: 0.739, thickness: 0.07", preformed packing, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS29513018 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5331-00-248-3848 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |

NO IMAGE
AVAILABLE

P/N MS29513-018 Specifications

| | |
|--------------------------------|---|
| Outside Diameter: | 0.879 Inches Nominal |
| Temp Rating: | -65.0 Deg Fahrenheit And 200.0 Deg Fahrenheit |
| Cross-sectional Height: | 0.067 Inches Minimum And 0.073 Inches Maximum |
| Center Hole Diameter: | 0.734 Inches Minimum And 0.744 Inches Maximum |
| Elongation Percentage: | 200 Maximum |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr |

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-018 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.