

## P/N MS29513-022

## **Description**

inner diameter: 0.986", thickness 0.070", preformed packing o-ring, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513022

Minimum Qty (MOQ): 25

NSN: 5331-00-250-0230

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-022 Specifications

Outside Diameter:	1.113 Inches Minimum And 1.145 Inches Maximum
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	0.983 Inches Minimum And 0.995 Inches Maximum
End Item Identification:	Gun,5-in./54 Cal, Mk-42&45;aircraft,(ac130h, Mc130h, Ec-130e, Hc-130
Material:	Rubber Butadiene-acrylonitrile Class Nbr

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-022">https://military-fasteners.com/o\_rings/o\_rings/MS29513-022</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-022">https://military-fasteners.com/o\_rings/o\_rings/MS29513-022</a> and selecting the quantity you want then click out <a href="https://military-fasteners.com/o\_rings/MS29513-022">https://military-fasteners.com/o\_rings/o\_rings/MS29513-022</a> and selecting the quantity you want then click out <a href="https://military-fasteners.com/o\_rings/MS29513-022">https://military-fasteners.com/o\_rings/o\_rings/MS29513-022</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-022">https://military-fasteners.com/o\_rings/MS29513-022</a> and selecting the quantity you want then click "add to cart".