

## P/N MS29513-026

## **Description**

inner diameter: 1.239", thickness 0.070", preformed packing o-ring, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513026


Minimum Qty (MOQ): 25


NSN: 5331-00-003-9157

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-026 Specifications

Outside Diameter:	1.362 Inches Minimum And 1.396 Inches Maximum
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	1.233 Inches Minimum And 1.245 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr
Material Document And Classification:	Mil-p-5315 Mil Spec Single Material Response

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-026">https://military-fasteners.com/o\_rings/o\_rings/MS29513-026</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-026">https://military-fasteners.com/o\_rings/o\_rings/MS29513-026</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-026">https://military-fasteners.com/o\_rings/o\_rings/MS29513-026</a> and selecting the quantity you want then click "add to cart".