

P/N MS29513-028

Military-Fasteners.com

Description

inner diameter: 1.364", thickness 0.070", preformed packing, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model:		MS29513028			
Minimum Qty (MOQ):		25			
NSN:		5331-00-265-1093			
ECCN:		EAR99			
National Motor Freight:		194120, Washers / Gaskets / Pckg Dvcs Noi			
\bigcirc			\bigcirc		
	<i>⊙ IMILITARY</i> ★	FASTENERS			

IIII.ITARY *FASTENERS www. Military-Fasteners.com

P/N MS29513-028 Specifications

Outside Diameter:	1.504 Inches Nominal		
Temp Rating:	-65.0 Deg Fahrenheit And 200.0 Deg Fahrenheit		
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum		
Center Hole Diameter:	1.358 Inches Minimum And 1.370 Inches Maximum		
Elongation Percentage:	200 Maximum		
Material:	Rubber Butadiene-acrylonitrile Class Nbr		

How to Order

Order this o-ring from our inventory online by visiting <u>https://military-fasteners.com/o_rings/0_rings/MS29513-028</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.