

## P/N MS29513-032

## **Description**

inner diameter: 1.864", thickness 0.070", preformed packing o-ring, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513032

Minimum Qty (MOQ): 25

NSN: 5331-00-481-9987

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-032 Specifications

Outside Diameter:	2.004 Inches Nominal
Temp Rating:	-65.0 Deg Fahrenheit And 200.0 Deg Fahrenheit
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	1.854 Inches Minimum And 1.874 Inches Maximum
Elongation Percentage:	200 Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/mS29513-032">https://military-fasteners.com/o\_rings/o\_rings/mS29513-032</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.