

P/N MS29513-033

Military-Fasteners.com

Description

inner diameter: 1.989, thickness: 0.070", preformed packing, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | MS29513033 |
|-------------------------|---|
| Minimum Qty (MOQ): | 25 |
| NSN: | 5331-00-410-4887 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |

MILITARY *****FASTENERS MILITARY *FASTENERS 0 www.Military-Fasteners.com

P/N MS29513-033 Specifications

| Outside Diameter: | 2.129 Inches Nominal |
|-------------------------|---|
| Cross-sectional Height: | 0.067 Inches Minimum And 0.073 Inches Maximum |
| Center Hole Diameter: | 1.979 Inches Minimum And 1.999 Inches Maximum |
| Elongation Percentage: | 200 Maximum |
| Hardness Rating: | 65.0 Shore Durometer A Nominal |
| Material: | Rubber Butadiene-acrylonitrile Class Nbr |

How to Order

Order this o-ring from our inventory online by visiting <u>https://military-fasteners.com/o_rings/o_rings/MS29513-033</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.