

P/N MS29513-035

Description

inner diameter: 2.239", thickness 0.07", preformed packing, hydrocarbon fuel resistant, MS29513 series oring

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online


Additional Information

SKU / Model: MS29513035

Minimum Qty (MOQ): 25

NSN: 5331-00-476-7406

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi







^{*} See page 2 for technical characteristics

P/N MS29513-035 Specifications

Outside Diameter:	2.355 Inches Minimum And 2.403 Inches Maximum
Cross-sectional Height:	0.067 Inches Minimum And 0.073 Inches Maximum
Center Hole Diameter:	2.229 Inches Minimum And 2.249 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-035 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29513-035 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/o_rings/MS29513-035 and selecting the quantity you want then click "add to cart".