

Description

inner diameter: 0.362", thickness 0.103", preformed packing, hydrocarbon fuel resistant, MS29513 series oring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513110
Minimum Qty (MOQ):	50
NSN:	5331-00-248-3837
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N MS29513-110 Specifications

Outside Diameter:	0.557 Inches Minimum And 0.579 Inches Maximum
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	0.357 Inches Minimum And 0.367 Inches Maximum
End Item Identification:	W/s: Guided Missile Launching System, Mk 26 (gmls); Fire Control System, Missile Mk 74 (fcs); Systems, Jp-5 Aviation Fuels; Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Boilers, 1200 Psi; Lpd 17 Class Amphibious Transport Dock; Fire Control System, Mk 92 (fcs); Engine, Aircrft, Tf33-100 (e3a/b/c); Shipboard Material Handling Equipment (mhe)
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-110 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.