

Description

inner diameter: 0.737", thickness 0.103", preformed packing, hydrocarbon fuel resistant, MS29513 series oring

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513116
Minimum Qty (MOQ):	50
NSN:	5331-00-248-3850
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS29513-116 Specifications

Outside Diameter:	0.928 Inches Minimum And 0.958 Inches Maximum
Temp Rating:	-70.0 Deg Fahrenheit And 180.0 Deg Fahrenheit
Cross-sectional Height:	0.100 Inches Minimum And 0.103 Inches Maximum
Center Hole Diameter:	0.732 Inches Minimum And 0.742 Inches Maximum
Hardness Rating:	70.0 Shore Durometer A Nominal
Material:	Rubber Butadiene-acrylonitrile Class Nbr
Material Document And Classification:	Mil-p-5315 Mil Spec Single Material Response

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-116 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.