

## P/N MS29513-124

## **Description**

inner diameter: 1.237", thickness 0.103", preformed packing o-ring hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513124

Minimum Qty (MOQ): 20

NSN: 5331-00-265-1074

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-124 Specifications

| Outside Diameter:       | 1.425 Inches Minimum And 1.461 Inches Maximum |
|-------------------------|---|
| Cross-sectional Height: | 0.100 Inches Minimum And 0.106 Inches Maximum |
| Center Hole Diameter:   | 1.231 Inches Minimum And 1.243 Inches Maximum |
| Material:               | Rubber Butadiene-acrylonitrile Class Nbr      |

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-124">https://military-fasteners.com/o\_rings/o\_rings/MS29513-124</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-124">https://military-fasteners.com/o\_rings/MS29513-124</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-124">https://military-fasteners.com/o\_rings/MS29513-124</a> and selecting the quantity you want then click "add to cart".