

Description

inner diameter: 1.424", thickness 0.103", preformed packing o-ring, hydrocarbon fuel resistant

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513127
Minimum Qty (MOQ):	25
NSN:	5331-00-265-1078
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N MS29513-127 Specifications

Outside Diameter:	1.612 Inches Minimum And 1.648 Inches Maximum
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	1.418 Inches Minimum And 1.430 Inches Maximum
End Item Identification:	W/s: Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Engine, Aircraft Tf33-pwpp-102 (c-135e, Ec-135h/k/p); Engine, Aircraft Tf33-p-3/5/9 (c/ec-135, B-52h); Engine, Aircraft, Tf33-100 (e3a/b/c); Helicopter, Hh-53h Pave Low; Aircraft, C-18a, Ec-18b; Engine, Aircraft, F100-pw-200 (f-16a/b/c/d); Engine, Aircraft, F100-pw-100 (f-15a/b/c/d); Engine, Aircraft, Tf-33-p-7 (c-141a/b)
Material:	Rubber Butadiene-acrylonitrile Class Nbr

How to Order

Order this o-ring from our inventory online by visiting https://military-fasteners.com/o_rings/o_rings/MS29513-127 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.