



Military-Fasteners.com

P/N MS29513-132

Description

inner diameter: 1.737, thickness: 0.103", preformed packing o-ring, hydrocarbon fuel resistant"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS29513132
Minimum Qty (MOQ):	10
NSN:	5331-00-265-1085
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS29513-132 Specifications

<b>Outside Diameter:</b>	1.922 Inches Minimum And 1.964 Inches Maximum
<b>Temp Rating:</b>	-70.0 Deg Fahrenheit And 180.0 Deg Fahrenheit
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	1.727 Inches Minimum And 1.747 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-132](https://military-fasteners.com/o_rings/o_rings/MS29513-132) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.