



★ FASTENERS

Military-Fasteners.com

P/N MS29513-148

## Description


inner diameter: 2.737", thickness 0.103", preformed packing o-ring, hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS29513148
Minimum Qty (MOQ):	25
NSN:	5331-00-541-2252
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



\* See page 2 for technical characteristics

## P/N MS29513-148 Specifications

<b>Outside Diameter:</b>	2.915 Inches Minimum And 2.971 Inches Maximum
<b>Cross-sectional Height:</b>	0.100 Inches Minimum And 0.106 Inches Maximum
<b>Center Hole Diameter:</b>	2.722 Inches Minimum And 2.752 Inches Maximum
<b>Material:</b>	Rubber Butadiene-acrylonitrile Class Nbr

## How to Order

Order this o-ring from our inventory online by visiting [https://military-fasteners.com/o\\_rings/o\\_rings/MS29513-148](https://military-fasteners.com/o_rings/o_rings/MS29513-148) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.