

# P/N MS29513-153

## **Description**

inner diameter: 3.487", thickness 0.103", preformed packing o-ring - hydrocarbon fuel resistant

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS29513153

Minimum Qty (MOQ): 10

NSN: 5331-00-875-8288

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS29513-153 Specifications

Outside Diameter:	3.663 Inches Minimum And 3.723 Inches Maximum
Cross-sectional Height:	0.100 Inches Minimum And 0.106 Inches Maximum
Center Hole Diameter:	3.472 Inches Minimum And 3.502 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr
Specification/standard Data:	80205as29513 Professional/industrial Association Standard

### **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/MS29513-153">https://military-fasteners.com/o\_rings/o\_rings/MS29513-153</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-153">https://military-fasteners.com/o\_rings/MS29513-153</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/MS29513-153">https://military-fasteners.com/o\_rings/MS29513-153</a> and selecting the quantity you want then click "add to cart".